

項目	品番	PD-40 PD-60 PD-70 PD-80 PD-90 PD-910													
		PD-01	PD-05	PD-1	PD-2	PD-4	PD-6	PD-7	PD-8	PD-9	PD-91	PD-10	PD-11	PD-12	PD-13
定格電流 (A)		1	1	1	1	1	1	1	1	1	1	1	1	1	1
接触抵抗 10mΩ以下		←	←	←	←	←	←	←	←	←	←	←	←	←	←
使用温度範囲 -40~+125℃		←	←	←	←	←	←	←	←	←	←	←	←	←	←
挿抜回数 100回以上		←	←	←	←	←	←	←	←	←	←	←	←	←	←
挿入力 (g以上)		10	10	70	70	70	70	50	70	20	20	70	50	20	20
抜去力 (g以上)		10	10	70	70	70	70	50	70	20	20	70	50	20	20
材質															
内部コンタクト…ベリリウム銅		←	←	←	←	←	←	←	←	←	←	←	←	←	←
ボディ…黄銅															

項目	品番	PD-310													
		PD-14	PD-31	PD-51	PD-61	PD-61A	PD-62	PD-63	PD-66	PD-71	PD-72	PD-73	PD-74	PD-77	PD-131
定格電流 (A)		1	3	1	5	3	5	5	5	5	5	5	5	5	15
接触抵抗 10mΩ以下		←	←	←	←	←	←	←	←	←	←	←	←	←	←
使用温度範囲 -40~+125℃		←	←	←	←	←	←	←	←	←	←	←	←	←	←
挿抜回数 100回以上		←	←	←	←	←	←	←	←	←	←	←	←	←	←
挿入力 (g以上)		20	50	70	150	70	150	150	150	150	150	150	150	150	100
抜去力 (g以上)		20	50	70	150	70	150	150	150	150	150	150	150	150	100
材質															
内部コンタクト…ベリリウム銅		←	←	←	←	←	←	←	←	←	←	←	←	←	←
ボディ…黄銅															

項目	品番	PD-132 PD-133 PD-151 PD-152 PD-155 PD-191 PD-192 PD-193 PD-194 PD-199 PDS-510										
		PD-132	PD-133	PD-151	PD-152	PD-155	PD-191	PD-192	PD-193	PD-194	PD-199	PDS-510
定格電流 (A)		15	15	15	15	15	20	20	20	20	20	1
接触抵抗 10mΩ以下		←	←	←	←	←	←	←	←	←	←	←
使用温度範囲 -40~+125℃		←	←	←	←	←	←	←	←	←	←	←
挿抜回数 100回以上		←	←	←	←	←	←	←	←	←	←	←
挿入力 (g以上)		100	100	100	100	100	150	150	150	150	150	70
抜去力 (g以上)		100	100	100	100	100	150	150	150	150	150	70
材質												
内部コンタクト…ベリリウム銅		←	←	←	←	←	←	←	←	←	←	←
ボディ…黄銅												



ソケットの内部構造図